Exercise 11: Spring-mass oscillations

Purpose: to investigate the oscillations of a vertical spring-mass system.

Introduction

The force of an ideal spring stretched in one dimension is characterized by Hooke's law,

$$F_{\rm s} = -k(x - x_{\rm eq}),$$

where $x_{\rm eq}$ is the equilibrium position. Setting the equilibrium position to zero, $x_{\rm eq}=0$, the force of a spring act

$$F_{\rm s} = -kx$$
.

Suppose a mass is attached to a single spring, and it is stretched away from the equilibrium position, $x_{\rm eq}=0$. If the mass attached to an ideal spring is released at its initially stretched position, $x_{\rm max}$, then the spring will oscillate between the minimum and maximum positions with simple harmonic motion. This motion is described using mathematical shorthand as

$$x(t) = x_{\text{max}} \cos(\omega t - \varphi)$$
,

where φ is the phase associated with the time we begin observing this harmonic motion.

The acceleration of the mass caused by the spring is described by the equation

$$a_x(t) = -x_{\text{max}} \omega^2 \cos(\omega t - \varphi)$$
.

The force of the spring acting on the mass as a function of time follows as

$$F_{\rm s}(t) = -x_{\rm max} m\omega^2 \cos(\omega t - \varphi)$$
,

which is also a simple harmonic function. Note that a vertical spring-mass system is subject to a gravitational force; however, this force is a constant, $F_g=mg$, and only changes the equilibrium position. Also note that dissipative forces will be present in *real* springs and the amplitude will reduce over long time scales.

Laboratory assignment

There will be two components to this laboratory assignment. The first part is concerned with the properties of a spring that is stretched by a hanging mass and allowed to hang in static equilibrium. The second part concerns oscillations of the spring-mass system.

Stretched spring in static equilibrium

- 1. Hang the spring on the force sensor attached to the vertical stand.
- 2. Measure and record the vertical distance, h, from the end of the spring to the floor.
- 3. Attach the 50 g hanger and add an additional 100 g mass for a total hanging mass of 150 g.
- 4. Measure and record the height at this new static position.
- 5. Calculate the magnitude of the displacement from equilibrium, $d = |h h_0|$.
- 6. Repeat this measurement for additional hanging masses totaling 300 g, 450 g, and 600 g.
- 7. Make a table similar to Table I and fill it in. Including your uncertainty estimate, Δd .

Table I: data for a vertical spring in static equilibrium.

mg (N)	<i>d</i> (m)	Δd (m)

- 8. Make a graph of mg vs. d. Be sure to include x-axis error bars using Δd .
- 9. Find $k \pm \Delta k$ by using the LINEST function to calculate the slope and uncertainty in the slope.

Oscillating spring-mass system

- 10. Start with a total of 600 g for the hanging mass.
- 11. Tare the force sensor after making the oscillations as small as possible while in equilibrium.
- 12. Stretch the spring a few centimeters and let the system oscillate.
- 13. Run the force sensor shortly after the system begins to oscillate and view the graph.
- 14. Measure and record the period of oscillation T from the graph and estimate the uncertainty ΔT .
- 15. Repeat this measurement for a total hanging mass of 450 g, 300 g, and 150 g.
- 16. Make a table similar to Table II and fill it in.

Table II: data for an oscillating vertical spring-mass system.

m (kg)	T (s)	ΔT (s)	ω (rad/s)	$1/\omega^2$ (s ² /rad ²)

- 17. Knowing that $\omega = \sqrt{k/m}$, graph m vs. $1/\omega^2$. No error bars are required for this graph.
- 18. Use the LINEST function to determine the slope and the uncertainty in the slope, $k \pm \Delta k$.

Additional analysis

- 19. Compare your values for the spring constant k. Do the ranges overlap? Explain.
- 20. A spring that follows Hooke's law will have an intercept of m/3 for your graph of m vs. $1/\omega^2$. Check the intercept and the uncertainty of your intercept for your m vs. $1/\omega^2$ graph. Does this value of m/3 fall within the range of your intercept? Conclude by stating how well your spring models a Hooke's spring.

Equipment list: vertical stand, tapered Hooke's spring, mass hanger, slotted weights, force sensor, laptop.